

WIRELESS COMMUNICATION C





MIPOT design, manufacture and sell Wireless Communication Modules using different protocols for many IoT sectors and applications in the worldwide markets

Mipot have been active in the electronics industry since 1973. This has made us a reliable supplier over the years.

Mipot offer a full range of wireless modules, developed in accordance with the technical regulations and country-specific laws, targeting many markets around the globe.

During the development of the module we solve all the technical issues related to the radio frequency. The quality of our products, along with the detailed documentation and very qualified

- and accessible technical support, enables a fast introduction of your products in the market.
- Mipot offer the newest wireless technology solutions for Internet of Things (IoT) and Low Power Wide Area Network applications (LPWAN).
- Mipot also serve the market by offering high-quality EMS and ODM service and it represents a one-stopshop for all customers, offering not only product development but also mass production and all the services related to it, from the material procurement to the personalized logistics.

## **Applications**

Using the technologies developed in our R&D during the last years now we can cover different sectors of IoT markets. The applications can be the standard RF modulation for the Home and Smart Building to the new smart lighting devices.

Our products and new projects have reached succesfully the mass production stage in the sectors of Smart Agriculture, Smart Meetering, Waste Management Systems passing throw the Renewable Energy Systems. Here you have a full panoramic of these possibile applications.

### Smart Lighting



Healthcare Monitoring System

LIGHTING

















Sensitivity:

**Output Power:** 

Power Consumption:

100 mA@+14 dBm

140 mA@+20 dBm

 $Z_{Z}$  Power Down: 2.2  $\mu$ A



#### **TECHNICAL CHARACTERISTICS**

- Micro on-board: ARM Cortex M4
- THE. LoRaWAN<sup>®</sup> / LoRa<sup>®</sup> / wM-Bus
- 0 LGA form factor with 52 pads
- 11.30 mm x 8.90 mm (Size)
- SubGHz frequencies (868 MHz ÷ 960 MHz)
- SPI, I2C, UART, LPUART (Peripheral Interfaces)
- Secure element (Optional)
- 40°C + 85°C (Temperature Range)
- Flash memory space: 128 kByte



All products have the same Form Factor & **Pin-Out** 



## Harness the power of IoT

### The Internet of Things (IoT) has transformed the way modern human lives.

Discover the main sectors in which it is possible to integrate the potential of a new MiP (Mipot IoT Protocols) wireless communication modules series in LPWAN low power wide area networks.



## **Developer Kits for single core**

The DevKits are a series of single boards for the development and test of **MiP series** 



Equipped with 3 pin strip connectors, the kit allows easy interfacing with all LGA pads on the MiP module via jump wires or a perfboard. The developer can use the Devkit both in host-based mode, connecting his own controller to the board, or as a stand-alone product exploiting the full potential of the MiP Series modules. The package includes a development board with SMA connector, a monopole antenna for 868 MHz and 915 MHz frequency bands and a reference sheet.

#### PRODUCT

30001505A 30001505B 30001505B 30001505C 30001505D 30001505F

 Smart Metering (Gas + Water + Electric metering) • Smart Cities • Smart Parking Smart Lighting Building management (Smart Building, Home Automation, Smart Home) • Smart Logistics Waste Management Renewable Smart Energy System Smart Asset Management in the utility market • IIoT (Industrial Internet of Things) • Smart Agriculture Fleet Tracking • Smart Mobility & Smart Car Oil & Gas Sector Healthcare Monitoring System

CODE	COUNTRIES	DESCRIPTION
EU	Еигоре	Developer Kit 32001505AEU
EU	Еигоре	Developer Kit 32001505BEU
US	USA, Canada	Developer Kit 32001505BUS
EU	Еигоре	Developer Kit 32001505CEU
EU	Еигоре	Developer Kit 32001505DEU
EU	Еигоре	Developer Kit 32001505FEU



#### **WORLDWIDE CHIP SOLUTION**



Worldwide frequency range SubGHz Frequencies, 868 MHz ÷ 960 MHz

=	Supported international networks
	Public: LoRaWAN <sup>®</sup> , Sigfox
	Private: LoRa® Modem, LoRa® Mipot, wM-Bus, Mioty

#### **TECHNICAL CHARACTERISTICS**

₽	Micro on-board: ARM Cortex M4 and M0+
tht	LoRaWAN <sup>®</sup> / LoRa <sup>®</sup> / wM-Bus
9	LGA form factor with 52 pads
	11.30 mm x 8.90 mm (Size)
₩₩	SubGHz frequencies (868 MHz ÷ 960 MHz)
À\$	SPI, I2C, UART, LPUART (Peripheral Interfaces)
	Secure element (Optional)
	– 40°C + 85°C (Temperature Range)

Flash memory space: 256 kByte



- Power consumption: YE 100 mA@+14 dBm 140 mA@+20 dBm
- 11.30 All products have the same
- Form Factor & **Pin-Out**
- $z_{z}^{z}$  Power Down 2.2  $\mu$ A



## **Dual Core Plus**



HIGH RADIO PERFORMANCE Top radio performance for Europe (+14 dBm) and USA (+20 dBm)



**LPWAN PROTOCOLS** wM-Bus, LoRaWAN<sup>®</sup>, LoRa<sup>®</sup> Mipot, LoRa<sup>®</sup> Modem, Sigfox, Mioty



**BUILT-IN-UP-TO-DATE IOT STACKS** 



### **Dual Core Structure**





**MULTI-PROTOCOLS IN ONE SINGLE CHIP** More protocols in one single MiP wireless module like: LoRaWAN<sup>®</sup> + LoRa<sup>®</sup> Modem, wM-Bus + LoRaWAN®



**SECURE ELEMENT Optional hardware secure element** on demand



WORLD WIDE SUBGHZ FREQUENCY BANDS

### Free memory space for custom firmware upload Dual Core CPU to increase the performance



- Dual Core ARM Cortex M4 + ARM Cortex M0+ inside the same hardware
- Reduction of PCB layers in your electronic board
- · Possibility to use the internal micro controller to drive the full electronic board
- Cost reduction of your BOM
- Size reduction of final electronic board



PRODUCT CODE	COUNTRIES	DESCRIPTION
30001506AEU	Еигоре	Developer Kit 32001506AEU - wM-Bus
30001506BEU	Еигоре	Developer Kit 32001506BEU - LoRaWAN®
30001506BUS	USA, Canada	Developer Kit 32001506BEU - LoRaWAN®
30001506CEU	Еигоре	Developer Kit 32001506CEU - LoRa® Mipot
30001506DEU	Еигоре	Developer Kit 32001506DEU - LoRa® Modem
30001506FEU	Еигоре	Developer Kit 32001506FEU - LoRaWAN® + LoRa® Modem
30001514HW	Еигоре	Developer Kit 32001514HW Dual Core

## Dev kits software interface

With the Developer Kit we provide a free software to interact with the device. This software is really easy to install on your laptop or PC.

#### MAIN FEATURES

- Easy access to MiP module features
- Communication management from/to the MiP module series
- One GUI for all MiP module family serving multiple connected modules
- Real Time log viewer
- Quick schematic and Command Reference tool

March In Colonial		LoBa WAN		
Module Selected		Radio Configuration Activation C	onfiguration   Module Information   Applic	ation Extra
Selected port:	COM29	Radio Configuration		
		Radio Parameters		
Baud rate: (bps)	9600 bps	' Class ( ):	0 - Class A 🛛 👻	
		1		
C	Open	DR/SF (KHZ):	0 - SF12/125 kHz *	
		Power (dBm):	0 - 14 d8m ~	
0	lose	480.05		Read
				( Case
		Customer DevEUI ( ):	1	
		Duty-Cycle ( ):		
	Σ	000000000000000000000000000000000000000	-	
		KX2 DR/SF (kHz):	0 - SF12/125 kHz ~	
	, and a second sec	RX2 Freq (Hz):		Write
	j j	Public Naturack ( h	-	
		Poole (itemore ().	<u>.</u>	
MIP	OT #	Retry Number (0-15):	3 ~	
		LinkCheck Timeout (s):		
		Module Parameters		
$\sim$		Data indicate timeout (ms):		Read
l nRa	IA/A N			
LOILO		Baud Rate (bps):	0 - 9600 bps *	Write
$\leq$		Factory Reset		
			Factory Reset	
			[	
		5		
E10-10-14 26	31 00029 -> 4	A-33-02-20-05-52		
E10-10-14 50				
F10:10:16.19				
F10:10:16.21				
F10-10-10 39				
F10-10-19 42	2] COM29 /- /	A-83-91-55-A3		
[10-10-20 62	31 00029	4-33-02-00-08-19		
F10:10:20.02	11 00029 /- /	A 07 00 00 05 07 00 00 0		
E10-10:20.00	<u>rj com2</u> 5 (* <i>k</i>	00 00 00 00 00 00 00 00 00 00 00 00 00		
[10:10:22.96	5] COM29 -> #			
[10:10:22.98	31 COM29 <- #			
[10:10:26.13	oj com29 -> A			
THE R. P. LEWIS CO., LANSING MICH.		W-84-04-02-00-00-00-9C		
[10:10:20.14				

### **EVALUATION KIT**



## **Carrier board**

### **COMING SOON**

#### MAIN FEATURES

- Arduino compatible System
- USB-C Connection with your laptop or PC
- Enviromental Sensors on board
- Compatible with all MiP Series Developer Kits
- Free of charge Software to interact with our Evaluation Kits

# Protocol based transceivers

This line of wireless communication modules integrates LoRaWAN<sup>®</sup>, LoRa<sup>®</sup>, wM-Bus protocols and IEEE 802.15.4 standard



**LoRaWAN®** compliant wireless protocol module



32001353



The Mipot LoRaWAN® transceivers integrate the LoRaWAN® protocol operating in the 868 MHz or 915 MHz SRD Bands. They are optimized for long range, low consumption applications, suitable for Low Power Wide Area Networks (LPWAN). Based on LoRa® RF Technology and LoRaWAN® protocol they provide ultra-long range spread spectrum communication and high interference immunity. The transceivers are dedicated for battery operated devices and allow a **low-cost** secure two-way communication for the IoT.

wM-BUS wireless transceiver



32001324



The Mipot Wireless M-Bus transceiver operates in the 868 MHz SRD Band. Thanks to its small LCC form factor and low power consumption this module allows the implementation of **highly integrated low** power (battery operated) solutions for water, gas, heat or electricity metering applications, both on meter or concentrator devices.

### **LoRa**<sup>®</sup> **MIPOT NETWORK** wireless protocol module





The LoRa® MIPOT NETWORK transceiver is a LoRa<sup>®</sup> Technology-based transceiver operating in the 868 MHz SRD Band. It's optimized for long range, low consumption applications, suitable for **low power networks**. In addition to its **unparalleled range**, spread spectrum modulation also allows great immunity to interferers.

### **IEEE 802.15.4** standard 2.4 GHz Transceiver



### **IEEE 802.15.4**

The 32001445 is a **2.4 GHz transceiver** that implements a physical layer of the IEEE 802.15.4 standard, optimized for ultra-low consumption applications, suitable for low power networks. Its spread spectrum modulation assures great immunity to interferers. This module works as a **RF modem**, allowing the implementation of point-to-point communication or more complex custom networks.









### TECHNICAL CHARACTERISTICS

LoRaWAN <sup>®</sup> / LoRa <sup>®</sup> / wM-Bus / IEE 802.15.4 - 2,4
26,00 mm x 15.50 mm (Size)
European 868 MHz or USA 915 MHz frequencie
UART (Peripheral Interfaces)
– 40°C + 85°C (Temperature Range)
– 115 dBm@wM-Bus – 135 dBm@LoRa®
+14 dBm@868 MHz + 20 dBm@915 MHz
50 Ω antenna pad
Power consumption: 100 mA@+14 dBm 140 mA@+20 dBm

PART NUMBER	COUNTRIES	PROTOCOLS	CERTIFICATIONS	DESCRIPTION
32001324	Europe	wM-Bus	CE	M-Bus protocol module – EU
32001345	Еигоре	LoRa®	CE	LoRa® Mipot protocol module – EU
32001345M	Еигоре	LoRa®	CE	LoRa® Modem protocol module – EU
32001353	Europe	LoRaWAN®	LoRa Alliance®, CE	LoRaWAN® protocol module – EU
32001409	USA	LoRaWAN®	FCC, LoRa Alliance®	LoRaWAN® protocol module – USA
32001445	World Wide	IEEE 802.15.4	CE	IEEE 802.15.4 standard module – EU



**IEEE 802.15.4** 



One of the most important things is that all this line of products have the same form factor and the same Pin-Out



All features of the Wireless M-Bus and LoRa® modules can be tested with our dedicated Evaluation Kit. The board provides easy access to module pin-out, power supply pins and SMA antenna connector. Usage flexibility is given by several power supply modes.

To reduce the time to market and ease the user application SW development, the Evaluation Kit comes with a built-in microcontroller.

Access pins on the board allow SW development to be managed by an external microcontroller and custom SW development environment.

PRODUCT CODE	COUNTRIES	DESCRIPTION
22000151	<b>F</b>	
33000151	Europe	Evaluation kit for the 32001324 - WM-Bus
33000158	Еигоре	Evaluation kit for the 32001345 - LoRa® Mipot
33000158M	Еигоре	Evaluation kit for the 32001345M - LoRa® Modem
33000159	Еигоре	Evaluation kit for the 32001353 - LoRaWAN®
33000162	USA	Evaluation kit for the 32001409 - LoRaWAN®
33000169	World Wide	Evaluation kit for the 32001445 - IEEE 802.15.4 standard

## Eva kits software interface

With the Evaluation Kit we provide a free software to interact with the device. This software is really easy to install on your laptop or PC.

#### MAIN FEATURES

- Easily test the on-board RF module
- Smart application with environmental sensors
- Uplink/Downlink test with RGB LEDs
- Real Time log viewer

## **USB** Dongle

The USB Dongle comes with the module of choice and an integrated chip antenna. It can be used to connect your tablet or PC with the evaluation kit or the related wireless system associated using our configuration and test software.

PART NUMBER	ТҮРЕ	PROTOCOL	COUNTRIES	FREQ. (MHz)	DESCRIPTION
32001373	USB DRIVE	wM-Bus	Europe	868	ANT INT 32001324
32001374	USB DRIVE	wM-Bus	Europe	868	ANT EXT 32001324
32001388	USB DRIVE	LoRa <sup>®</sup> Mipot	Europe	868	ANT INT 32001345
32001388M	USB DRIVE	LoRa <sup>®</sup> Modem	Europe	868	ANT INT 32001345M



32001345 MipotLoRa DE	MO							-		
OM SETTINGS			Radio Config	TEST A	S Config	Network Config	TX Applica	tion		
COM SELECTION	COM3		Unicast							
BAUDRATE	115200		AD	DRESS (HI	EX)	Rx Data				
			3412000	0	~	Temp(°C)	25	Hum(%)	50	
Clos	e					Light(lx)	0	U	0	
			UP	DATE LIST			20			
						Cnt	30	VDat(V)	3,4	
			RED							
			00550					1100.0		
			GREEN					UPDA	IE HGB	
			BLUE		-					
						Current color is: (4	7, 19 ,47)			
	8		Broadcast	_						
	Wew		RED							
	O HO		GREEN					UPDA	TE RGB	
MIPO	)T 🗄		BLUE							
ATE/TIME:14/09	/2022 12:	23:13:								
A532100D1FF070	000123441	10000	00160D000	9A8610	00500	300000000	000002F1	32FB8		
ATE/TIME:14/09	/2022 12:	23:43:								
A532100D3FF080 ATF/TTMF:14/09	/2022 12:	24:13:	000800000	948610	888280	.3000000000	000002F1	32FBF		
A532100DBFF060	000123441	1160000	00160D000	9A8610	00500	3000000000	000002F1	32FAD		
										_

# Wireless Transparent Modules

Mipot offer a wide portfolio of transmitter, receiver and transceiver RF modules suitable for all short and long range applications that meet the technical regulations and laws applicable in different regions and market segments: Home Automation, Alarm System, Industrial, Smart Metering, Thermoregulation, Lighting, Ambient assisted living, Renewable Energies.



Tran	sceivers	ТҮРЕ	MOD.	FREQ. (MHz)	VS (V)	DESCRIPTION
	32001534	тнт	FSK	433,92	3	DUAL CHANNEL
	32001535	тнт	FSK	868,30	3	DUAL CHANNEL
	32001536	тнт	FSK	913,70	3	DUAL CHANNEL (US)
	32001537	тнт	FSK	449,85	3	SINGLE CHANNEL (Japan)
	32001538	тнт	FSK	447,875	3	DUAL CHANNEL (Korea)
	32001539	SMD	ООК	433,92	3	DUAL CHANNEL
	32001540	SMD	FSK	868,30	3	DUAL CHANNEL
	32001541	SMD	FSK	915	3	DUAL CHANNEL
	32001542	SMD	FSK	449.85	3	SINGLE CHANNEL

Receive	ers	ТҮРЕ	MOD.	FREQ. (MHz)	vs (v)	DESCRIPTION
	32001366 32001366F	тнт	FSK	433,92 868,30	3-5	SUPER HETERODYNE, WITH F-END, WITH ANTIGLITCH
	32001368F	SMD	FSK	868,30	3-5	High performance SMD Super Heterodyne
	32001414 32001415	тнт	ASK	433,92	5	F.END-antiglitch-RSSI
	32001520 32001520V3	тнт	ASK	433,92	5 3	RX 434 MHz ASK 5V RX 434 MHz ASK 3V
	32001522 32001522V3	тнт	ASK	433,92	5 3	Mini RX 434 MHz ASK 5V Mini RX 434 MHz ASK 3V
	32001548	SMD	ASK	433,92	5	RX SMD ASK 433.92MHZ 5V +F.END
	32001252	тнт	ASK	433,92	5	SUPER REGENERATIVE NARROW BAND SHIELDED
Transm	hitters	ТҮРЕ	MOD.	FREQ. (MHz)	VS (V)	DESCRIPTION
	32001151 32001151V3	тнт	ООК	433,92	5 3	Compact SAW
	32001371	SMD	ООК	433,92	3	PLL TRANSMITTER
	32001372	SMD	FSK	868,30	3	PLL TRANSMITTER
	32001387 32001387F	тнт	ООК	433,92 868,30	5	SAW transmitter OOK SAW
	32001387FV3 32001387V3	тнт	ООК	868,30 433,92	3	OOK SAW SAW transmitter



This is a set of products designed for home and building automation and consists in a series of receivers and remote controls for applications such as access control, temperature and lighting control, windows blinds and alarm systems.

Accessories		ТҮРЕ	FREQ. (MHz)	MOD.	VS (V)	DISTANCE (m) - free space -
	32001034HCS	Receiver	434	ASK	12 / 24	150
	33000145MIP	Receiver	434	ООК	100-250	150
2014 - POWER MILE 1 2 3 4 5 	33000148MIP	Receiver	434	ООК	100-250	150
	32001320	Transmitter	434	ООК	3	
	32001369A	Remote controller	434	ООК	12	
•••	32001369	Remote controller	434	ООК	12	

#### **OUR SERVICES**



### **EMS Electronic** Manufacturing Services

With many years of experience in the EMS (Electronic Manufacturing Services) field, we offer our services to many customers, from the multinational to small start-up in different sectors as Industrial, Home & building automation, Internet of Things (IoT), Meetering and many more.

**Mipot** is your technological partner that **guarantees** reliability and competence to turn your ideas into projects and products. We guarantee both low volumes with high-mix and high volumes with competitive costs.

#### **OUR SERVICES**



**ODM** Original Design Manufacturer Mipot offers **high quality ODM** (Original Design Manufacturing) services for the design, prototyping and mass production of electronic boards for Wireless communication devices and the integration of electronic systems.

support the customer in all stages of product development, starting from the specifications to the selection of the most appropriate components with the best performance and costs, passing to the engineering and manufacturing. Mipot offer the newest wireless technology solutions for Internet of Things (IoT), Machine to Machine (M2M) and other Low Power Wide Area Network applications (LPWAN) to be integrated in the customer product.

**COMPONENT PROCUREMENT** Supplier management, Vendor Rating and Scounting MATERIALS Incoming inspection, automatic component management

TRACEABILITY PCB laser marking. Batch traceability and single reel traceability with automatic

warehouse system

SMD ASSEMBLY 3 Yamaha lines, component size down to 009–005, 100% end of line TRI automatic AOI

THT ASSEMBLY Mounting, preforming, insertion THT components, wave and selective soldering, laser soldering

DEPANELING

Automatic depaneling by laser, manual depaneling with rotary cutter and punch cutter **CONFORMAL COATING** Selective, immersion, spray conformal coating

**FUNCTIONAL TEST** Automatic and Manual Test, Burn-In, customized **Run-In Test** 

**FULL SYSTEM ASSEMBLY** Low and flexible volumes

8

10

12

**QUALITY INSPECTION** TRI automatic AOI Inspection, New X-Ray machine inspection, Standard Quality department Inspection for all the lots in production

PACKAGING AND GLOBAL DISTRIBUTION Packaging upon customer specifications & worldwide fast delivery and Scounting

AFTER SALES SUPPORT

Product assurance, Maintance, problem solving and analysis



**ANTENNA DESIGN** We offer PCB or stand alone antenna design using EM simulation suite and anechoic chamber for final measurments

**PRE-COMPLIANCE TEST** Mipot can provide a full service of



**CO-DESIGN & PROTOTYPING** Mipot offers its experience for co-design and rapid internal prototyping



Our purchase department and R&D can provide this service for new design and new projects

With our experienced and highly motivated technical staff Mipot



pre-compliance tests of your device



**CERTIFICATION SUPPORT** We support our customers in the certification process of their products by managing relationships with external laboratories

WIRELESS SYSTEM INTEGRATION Mipot has developed considerable knowledge in the field of wireless system integration



 $\bigcirc$ 

### MIPOT S.p.A.

via Corona, 5 34071 Cormons Gorizia – Italy

PHONE +39 0481 630200

EMAIL mipot@mipot.com

> WEBSITE **mipot.com**

MIP SERIES mip.mipot.com

f







ంం

0

0